




Key Selling Point

- Extreme performance derives from Pioneer's Championship-winning SPL subwoofers.
- The versatile subwoofer lineup provides for various types of installation.

Main Specifications

Max. Music Power	1400 W
Nominal Music Power	400 W
Frequency Response	20 Hz to 125 Hz
Sensitivity	95dB
Impedance	4Ωx2
Size	30 cm





channeled for optimal ventilation to ensure a quick response and clear reproduction of bass.

Air Vent The movement of air within the subwoofer is smoothly


■ IMPP Composite Cone

An extremely rigid yet lightweight cone is vital to prevent cone failure at high sound pressure levels. Pioneer's IMPP Composite Cones meet this need perfectly. CAE (computer-aided engineering) has been applied to create a surface spoke design that ensures high durability and rigidity of the cone.

Fully Enclosed Basket

Magnetic circuit is tightly fixed to the basket to suppress undesirable sound-distorting recoil to the cone, realize clear and punchy bass sound.

TS-W310D4



TS-W311D4



4-Layer Copper Voice Coil with Aluminum Former

Aluminum former improves heat dissipation.

Dual-Layer Elastic **Polymer Surround**

- Features the world's first technology
- Dramatically improves durability and lightness, for superior response, especially for louder volume.

Independent Spider Holder

The TS-W311D4 has a feature inherited from Pioneer's competitiondominating SPL subwooferindependent spider holder that is separate from the basket. By preventing propagation of spider vibration through the basket to the cone, this structure improves high transient and linearity of excursion, enhances clarity of sound reproduction.


TS-W310D4



TS-W311D4



Dimension



For more information please visit www.pioneer-mea.com

Year of Release: 2016

Pioneer, Gulf Free Zone Dubai, U.A.E. Email: support@pioneer-uae.com www.pioneer-mea.com

Corporate web: www.pioneer.jp

